



राष्ट्रीय फैशन प्रौद्योगिकी संस्थान, कन्नूर

(वस्त्र मंत्रालय, भारत सरकार)

National Institute of Fashion Technology, Kannur

Ministry of Textiles, Government of India

(An ISO 9001:2008 Certified Institute)

File No.49/NIFT/KAN/ADMIN/Sewage Plant/2012 (PART-III)

04.05.2022

QUOTATION NOTICE

NIFT – Kannur invites quotations from the suppliers and service providers of Self Priming Mono Block Pump. Intending vendors who have GST registration may submit the quotation in the proforma enclosed (**Annexure I**) and submit the same by hand /post/courier so has to reach the National Institute of Fashion Technology, NIFT Campus, Mangattuparamba, Kannur-670562 on or before 11.05.2022,5.30PM.

Terms & Conditions

1. All-inclusive (Taxes, duties, transportation, loading, unloading charges, etc.) rates to be quoted.
2. The items shall be delivered and serviced within 7 days of the issue of the purchase order at NIFT, Kannur campus.
3. NIFT, Kannur will provide GST No. based on that GST invoice should be raised.
4. Payment will be made within 10 days against satisfactory supply and installation of the items by the competent authority.

Nayana
9/5/22

ASSISTANT DIRECTOR

Copy for display on the notice board as per the list:

1. Municipal office, Anthoor.
2. Village office , Morazha.
3. NIFT, Kannur Notice Board.

डिजाइन मैनेजमेंट और प्रौद्योगिकी का महाविद्यालय
A Premier Institute of Design, Management and Technology
Set up under an Act of Parliament

निफ्ट कैंपस, धर्मशाला, कन्नूर (पि.ओ.), कन्नूर, केरल-670562
NIFT Campus, Dharmashala, Kanoor (P.O), Kannur, Kerala - 670 562
Phone : 0497 2784781 to 0497 2784786 Email: info.kannur@nift.ac.in

Quotation for supply and installation of Self Priming Mono Block Pump as per specification and quantity noted below;

SL. NO	ITEM DESCRIPTION	QTY	UNIT PRICE (RS.)	GST (RS.)	TOTAL AMOUNT (RS.)
01	Capacity-1HP/0.75KW Head-11.5 mtr. Size- 40x40mm. Speed -2700 R.P.M Head Range-6.5-13 LPS. Phase- 3-Phase. Voltage-415V Frequency- 50Hz. Inlet/outlet- /50mm	01 Nos.			
02	Capacity-3HP/2.2KW Head-12/25.5 Mtr. Size- 50x50mm. Speed -2900 R.P.M Head Range-560-/80 LPS. DIS-560/80 lps Phase- 3-Phase. Voltage- 415V & 50Hz. Frequency-50Hz. Inlet/outlet- 63mm.	02 Nos.			
03	Capacity-5HP/3.7KW Head-12/25.5 Mtr. Size- 80x80mm. Speed -1450 R.P.M Head Range-9-/19.5 LPS. DIS-1125/400 Phase- 3-Phase. Voltage- 415V & 50Hz. Frequency-50Hz. Inlet/outlet- 90mm.	01 Nos.			
04	Installation charges				
Total Amount (Rs.)					

*GST registration copy should be enclosed along with the quote.

Supplier Name:

Signature with office seal:

Contact Number: